


PRODUCT FEATURES

- Ultrafast Reverse Recovery Time
- Soft Reverse Recovery Characteristics
- Low Reverse Recovery Loss
- Low Forward Voltage
- High Surge Current Capability
- Low Leakage Current



APPLICATIONS

- Inversion Welder
- Uninterruptible Power Supply
- Plating Power Supply
- Ultrasonic Cleaner and Welder
- Converter & Chopper
- PFC



ABSOLUTE MAXIMUM RATINGS($T_C=25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter/Test Conditions		Values	Unit
V_R	Maximum D.C. Reverse Voltage		200	V
V_{RRM}	Maximum Repetitive Reverse Voltage			
$I_{F(AV)}$	Average Forward Current	$T_C=80^\circ\text{C}$, Per Diode	200	A
		$T_C=80^\circ\text{C}$, Per Moudle	400	
$I_{F(RMS)}$	RMS Forward Current	$T_C=80^\circ\text{C}$, Per Diode	282	
I_{FSM}	Non Repetitive Surge Forward Current	$T_J=45^\circ\text{C}, t=10\text{ms}, \text{Sine, peak value}$	2000	
		$T_J=45^\circ\text{C}, t=8.3\text{ms}, \text{Sine, peak value}$	2200	
I^2t	For Fusing	$T_J=45^\circ\text{C}, t=10\text{ms}, \text{Sine, peak value}$	20000	A^2S
		$T_J=45^\circ\text{C}, t=8.3\text{ms}, \text{Sine, peak value}$	20086	
P_D	Power Dissipation		370	W
T_J	Junction Temperature		-40 to +150	$^\circ\text{C}$
T_{STG}	Storage Temperature Range		-40 to +125	$^\circ\text{C}$
V_{isol}	Isolation Breakdown Voltage	AC, 50Hz(R.M.S), $t=1\text{minute}$	3000	V
Torque	Module to Sink	Recommended (M5)	2.5~4	Nm
Torque	Module Electrodes	Recommended (M5)	2.5~4	Nm
R_{thJC}	Junction to Case Thermal Resistance(Per Diode)		0.34	$^\circ\text{C }/\text{W}$
Weight			100	g

MacMic Science & Technology Co., Ltd.

Add: #18, Hua Shan Zhong Lu, New District, Changzhou City, Jiangsu Province, P. R .of China

MMF400N020DK2B

ELECTRICAL CHARACTERISTICS ($T_c = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter/Test Conditions	Min.	Typ.	Max.	Unit
I_{RM}	Maximum Reverse Leakage Current	$V_R = 200\text{V}$		1	mA
		$V_R = 200\text{V}, T_J = 125^\circ\text{C}$		10	
V_F	Forward Voltage	$I_F = 200\text{A}$		0.9	V
		$I_F = 200\text{A}, T_J = 125^\circ\text{C}$		0.8	
t_{rr}	Reverse Recovery Time ($I_F = 1\text{A}$, $dI_F/dt = -200\text{A}/\mu\text{s}$, $V_R = 30\text{V}$)		42		ns
t_{rr}	Reverse Recovery Time	$I_F = 200\text{A}, V_R = 100\text{V}$,	135		ns
I_{RRM}	Maximum Reverse Recovery Current	$dI_F/dt = -200\text{A}/\mu\text{s}$		15.5	A
t_{rr}	Reverse Recovery Time	$I_F = 200\text{A}, V_R = 100\text{V}$,	195		ns
I_{RRM}	Maximum Reverse Recovery Current	$dI_F/dt = -200\text{A}/\mu\text{s}, T_J = 125^\circ\text{C}$		23	A




Figure 1. Forward Voltage Drop vs Forward Current




Figure 2. Reverse Recovery Time vs dI_F/dt




Figure 3. Reverse Recovery Current vs dI_F/dt




Figure 4. Reverse Recovery Charge vs dI_F/dt







Figure 5. Forward current vs Case temperature



Rectangular Pulse Duration(S)
Figure 6. Transient Thermal Impedance



Dimensions in (mm)

Figure 7. Package Outline